

W10IB3S-PCH2AC-POE

10.1" Intel® Celeron® N2930 S系列人機介面工業電腦



KEY FEATURES

- 10.1" 1280 x 800 解析度 投射電容式多點觸控 (PCAP)
- Intel® Celeron® N2930 處理器低功耗系統
- 無風扇冷卻系統和超低功耗
- 雙千兆乙太網路
- 前面板IP65防水防塵
- RGB LED燈條指示器, 在兩側
- 支持PoE功能
- 可選HF RFID讀取器
- 可選2MP前置攝像頭
- 房間預訂時間表, 訪問控制, 房間信息顯示




SPECIFICATIONS

顯示器			
解析度	1280x800	尺寸	10.1 inches
對比度	800:1	面版亮度	350 nits 1000 nits(Optional)
可視角	85,85,85,85	可視區	216.96 x135.6 mm
類型	Projected Capacitive Multi Touch Screen		
系統規格			
處理器	Intel® Celeron® N2930 (2M Cache, up to 2.16 GHz)	記憶體	1 x SO-DIMM, DDR3L 1600 MHz, 4GB 8GB (Optional)
儲存空間	1 x M.2 2242 B-key SSD 128GB. M.2 2242 B-key SSD up to 512GB. (Optional)	以太網控制器	2 x Intel® Gigabit Ethernet Controller
作業系統	Windows 10 IoT Enterprise (Optional) Linux Ubuntu 18.04 (Optional)	無線通訊網路	Support (Optional)
藍牙	Support (Optional)	無線射頻辨識	HF RFID Reader 13.56 MHz (Optional)
Light Bar	Built-in RGB LED Status Light Bar, on both sides		
機構			
外觀尺寸	264.57 x 173.29 x 35.7 mm	安裝	Panel mount VESA Mount
外殼	Metal Housing	冷卻系統	Fanless design
嵌入尺寸	250x159mm		
環境			
工作濕度	10% to 90% (non-condensing)	工作溫度	0~50°C
儲存溫度	-20~60°C	IP防水等級	Front IP65
認證			
認證	CE, FCC		
訊號埠			
電源輸入	1 x 12V DC, 3-Pin Terminal Block	USB埠	1 x USB3.0 (Type-A) 1 x USB2.0 (Type-A)
序列埠	1 x RS232/422/485 (Default RS232)	音訊	1 x Speaker

擴充端口	2 x M.2 slot(1 for WiFi, 1 for SSD)	有線網路	2 x Giga LAN RJ45 Connector, One with PoE(PD, 802.3at)(Optional)
配件			
配件	100~240V AC to DC Adapter Power Cord Terminal Block to 2.5Ø Female Adapter Cable Open Wire Cable with terminal block connector Driver CD & Manual VESAscrews	配件選配	VESA Wall Mount (Optional) VESA Desk Stand (Optional) Glass Wall Mount Kit (Optional) Front Side Wall Mount (Optional) VESA bracket mounting kit (Optional)
電源			
電源規格	12V DC 10~60V (Optional)	電源適配器	12V 50W
POE	PoE (PD): follows IEEE 802.3at (25 W)		

DIMENSIONS UNIT:MM

Winmate W10IB3S-PCH2AC-POE



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
3. All specifications are subject to change without prior notice.